

FIK Series

640*480mm, Indoor LED



Shenzhen Senlar Vision Technology CO., Ltd.

www.senlar.com

Features:

- Cable-less design minimizes clutter, ensuring a cleaner setup.
- Excellent surface flatness for seamless displays, making installation and disassembly quick and easy.
- Designed for easy wall mounting, making them ideal for projects that require displays to be mounted on walls.
- Able to transform to LED Poster and floor standing LED TV.

Usage Precautions:

- Static Protection: When handling the LED lamp panel and display panel, take precautions against static electricity by following these protective measures:
 - Wear grounded anti-static wrist straps or anti-static gloves.Ensure that the display body is properly grounded, with the grounding resistance ≤ 10 ohms. Perform a check every six months.
- Cleaning: When cleaning the surface of the lamp panel, do not use unknown chemical liquids. Use a clean, dust-free or damp cloth with purified water for gentle wiping.
- Power Protection: The distribution box must be equipped with surge protectors and other protective devices.

Specifications

Pixel Pitch	1.25	1.53	1.86	2	2.5
LED Type	SMD1010	SMD1515	SMD1515	SMD1515	SMD2121
Module Resolution	256*128	208*104	172*86	160*80	128*64
Cabinet Resolution	512*384	416*312	344*258	320*240	256*192
Density(dots/m ²)	640000	422500	288906	250000	160000
Scan Method	1/64	1/52	1/43	1/40	1/32
Module Size(mm)	320*160				
Cabinet Size(mm)	640*480*49				
Cabinet Weight(kg)	7				
Brightness (nit)	>800				
Color Temperature (K)	3000-18000K				
Viewing Angle	160°/160°				
Contrast Ratio	>10000:1				
Power Consumption(W/m ²)	250-600				
Refresh Rate (Hz)	3840				
Gray Level (bit)	16				
IP Level	IP30				